

AUTOTROL VALF MODELLERİ

Evsel



368

255

255 Logix

| | 368 | 255 | 255 Logix |
|--|--------------------|------------------------------|------------------------------|
| Valf Materyali | Glass Filled Noryl | Glass Filled Noryl | Glass Filled Noryl |
| Giriş / Çıkış Boyutu | 3/4", 1" | 1/2", 3/4", 1", 22 mm, 32 mm | 1/2", 3/4", 1", 22 mm, 32 mm |
| Servis Debisi (m ³ /gpm) | 3.8/16.6 | 3.5/15.5 | 3.5/15.5 |
| Ters Yıkama Debisi (m ³ /gpm) | 0.6/2.73 | 1.4/6 | 1.4/6 |
| Max. Yumuşatma Tank Boyutu | 10" | 14" | 14" |
| Max. Filtre Tank Boyutu | 6" - 10" | N/A | N/A |
| Rejenerasyon Tipi | Downflow | Downflow | Downflow |
| Program Ayarı | ● ¹ | ● ² | ● ³ |
| Dublex | | | ● |
| Multiplex | | | ● |
| Drenaj Hattı | 1/2" | 1/2", 3/8" | 1/2", 3/8" |
| Tuz Emiş Hattı | 3/8" | 3/8" | 3/8" |
| Difüzör Borusu Yüksekliği (Boğazdan) | 13 +/- 13 mm | 29 +/- 3 mm | 29 +/- 3 mm |
| Difüzör Borusu Çapı | 1.05" | 1.05" | 1.05" |

Endüstriyel



Performa

Performa CV

Magnum

| | Performa | Performa CV | Magnum |
|--|------------------------|------------------------|--------------------|
| Valf Materyali | Glass Filled Noryl | Glass Filled Noryl | Glass Filled Noryl |
| Giriş / Çıkış Boyutu | 3/4", 1", 22 mm, 32 mm | 3/4", 1", 22 mm, 32 mm | 1/2", 2" |
| Servis Debisi (m ³ /gpm) | 5.7/25 | 5.7/25 | 17.3/76 |
| Ters Yıkama Debisi (m ³ /gpm) | 4.5/20 | 4.5/20 | 20.2/89 |
| Max. Yumuşatma Tank Boyutu | 14" | 21" | 42" |
| Max. Filtre Tank Boyutu | 6" - 24" | 6" - 24" | 14" - 36" |
| Rejenerasyon Tipi | Downflow/Upflow | Downflow | Downflow |
| Program Ayarı | ● ³ | ● ³ | ● ³ |
| Dublex | | ● | ● |
| Multiplex | ● | ● | ● |
| Drenaj Hattı | 3/4" | 3/4" | 1/2", 2" |
| Tuz Emiş Hattı | 3/8" | 3/8" | 1/2" |
| Difüzör Borusu Yüksekliği (Boğazdan) | 13 +/- 13 mm | 13 +/- 13 mm | 6 - 9 mm |
| Difüzör Borusu Çapı | 1.05" | 1.05" | 1.5" |

●¹ 4 Farklı Program

●² 3 Sabit Program (59/90/118')

●³ Programlanabilir çevrimler (1'den 299'a kadar)

AUTOTROL CONTROL VALVES



QUALITY

All Autotrol valves have been certified by major EU certificates: CE, 206 / 95 / EC low voltage, 2004 / 108 / EC electromagnetic compatibility, ACS, WRAS and DM174. On top of that, our Pisa plant is ISO 9001:2008 certified.

OPERATING PRINCIPLE

Autotrol valves are characterized by their principle of operation: flappers actuated by the cams of the camshaft. The advantage being frictionless seals, no parts subject to wear inside the valve, ease of maintenance, longer service intervals and longer life cycle of the valve.

LOGIX 700 SERIES CONTROLLERS

740

Residential electronic time-clock controller for single-tank filter or softener applications up to 14-inch diameter tanks.

742

Commercial & industrial electronic timeclock controller for single filter or softener applications up to 42-inch diameter tanks, with fully programmable cycle times.

760

Residential electronic metered-demand (volumetric) controller for single-tank filter or softener applications up to 14-inch diameter tanks.

762

Commercial & industrial electronic metered-demand (volumetric) controller for single filter or softener applications up to 42-inch diameter tanks, with fully programmable cycle times.

764

Commercial & industrial electronic metered-demand (volumetric) controller for single filter or softener applications up to 42-inch diameter tanks, with fully programmable cycle times.

It is also suited for multi-tank applications such as twin alternating, twin parallel, single tank remote regeneration start and multi single tank lockout capability for softeners and filter control.

UYARLAMA

Today, with our Logix 700 series controllers, we are able to develop proprietary software, perfectly adapted to all customers' needs.

INOVASYON

Our research and product development has continuously led to improve the earliest idea behind our foundation and the techniques for its application to your needs.